

1 Introduction

This document contains the following listings:

Listings

2 Inline Listings

Various delimiters: `a_word`, `a_word`, `a_word`, `a_word` and even `a_word done`.

Indirectly: `a_word`; and with messed up braces `foo { bar .`

And also as an environment: `_word`; `done`.

3 An untyped Listing

No options, language, etc

```
1 stuff1
2 stuff2
3 stuff3
```

4 Some C

```
1 #define EXAMPLE whichwhat
2 x = "foo";
3 break;
```

5 A Pascal Listing

A listing portion:

```
1 begin
2   { do nothing }
3 end;
```

A numbered listing:

```
1 for i:=maxint to 0 do
  begin
3   { do nothing }
  end;
5
Write('case_insensitive');
7 Write('long_string');
Write('Pascal_keywords.');
```

A Titled listing:

A bit of Pascal

```
1  for i:=maxint to 0 do
2  begin
3    { do nothing }
4  end;
5  Write('case_insensitive');
```

A Captioned listing (known as Listing ??) :

Listing 1: Another bit of Pascal

```
100 for i:=maxint to 0 do
101 begin
102   { do nothing }
103 end;
```

6 An Environment

```
1  for i:=maxint to 0 do
2  begin
3    { do nothing }
4  end;
```

```
for i:=maxint to 0 do
begin
  { do nothing }
end;
```

1
2
3
4

```
for i:=maxint to 0 do
begin
  { do nothing }
end;
```

1
2
3
4

7 Framing and such

```
1  for i:=maxint to 0 do
2  begin
3    { do nothing }
4  end;
```

```
1  for i:=maxint to 0 do
2  begin
3    { do nothing }
4  end;
```

```

1  for i:=maxint to 0 do
2  begin
3    { do nothing }
4  end;

```

```

1  for i:=maxint to 0 do
2  begin
3    { do nothing }
4  end;

```

Listing 2: A C language listing

```

1  #define EXAMPLE whichwhat
2  x = "foo";
3  break;

```

8 Listing with Math

```

1  // calculate  $a_{ij}$ 
2  a[i][j] = a[j][j]/a[i][j];

```

```

1  // calculate  $a_{ij}$ 
2  a[i][j] = a[j][j]/a[i][j];

```

```

1  // calculate  $a_{ij}$ 
2   $a_{ij} = a_{jj}/a_{ij}$ ;
3  // calculate  $a_{ij} = \sin x$ 
4
5  a[i,j]=sin(x)
6  foo="a_word";
7  foo="a_x^2 math";

```

```

1  // calculate  $\langle a_{ij} \rangle$ 
2  a_{ij}
3  = a_{jj}/a_{ij};

```

```

1  // calculate  $\$a_{ij}\$$ 
2  $a_{ij}
3  = a_{jj}/a_{ij}$;
4  // calculate  $\$a_{ij} =$ 
5   $\sin x\$$ 
6  a[i,j]=sin(x)
7  foo="a_word";
8  foo="a_\string";
9  foo="a_x^2_math";

```

9 A Perl Listing

```
1  # -- CPERL --
2  package LaTeXML::Package::Pool;
3  use strict;
4  use LaTeXML::Package;
5
6  DefConstructor( '\container{}', "<ltx:special>#1</ltx:special>" );
7  DefConstructor( '\foo', "<ltx:not-defined/>" );
8
9  1;
```

10 A Recursive T_EX listing

```
1  \documentclass{article}
2  \usepackage{makeidx}
3  \makeindex
4  \usepackage{listings}
5  \usepackage[dvipsnames]{color}
6  \begin{document}
7  \lstset{numbers=left}
8  \section{Introduction}
9  This document contains the following listings:
10 \lstlistoflistings
11
12 \section{Inline Listings}
13 Various delimiters: \lstinline{a_word},
14 \lstinline!a_word!, \lstinline Aa_wordA,
15 \lstinline&a_word& and even \lstinline^a_word^ done.
16
17 \def\justcopy#1{#1}
18 Indirectly: \justcopy{\lstinline|a_word|};
19 and with messed up braces \lstinline{foo { bar }.% }
20
21 And also as an environment:
22 \begin{lstinline}
23 a_word
24 \end{lstinline}; done.
25 \section{An untyped Listing}
26 No options, language, etc
27 \begin{lstlisting}
28 stuff1
29 stuff2
30 stuff3
31 \end{lstlisting}
```

```

32
33 \section{Some C}
34
35 \begin{lstlisting}[language=C,identifierstyle=\slshape,directivestyle=\ttfamily]
36 #define EXAMPLE whichwhat
37 x = "foo";
38 break;
39 \end{lstlisting}
40
41 \section{A Pascal Listing}
42 A listing portion:
43 \begin{lstlisting}[language=Pascal,firstline=2,lastline=5,caption={}]
44 for i:=maxint to 0 do
45 begin
46   { do nothing }
47 end;
48
49 Write('case insensitive ');
50 Write('long ' ' string ');
51 Write('Pascal keywords. ');
52 \end{lstlisting}
53
54 A numbered listing:
55 \begin{lstlisting}[language=Pascal,numbers=left, numberstyle=\tiny, stepnumber=2]
56 for i:=maxint to 0 do
57   begin
58     { do nothing }
59   end;
60
61 Write('case insensitive ');
62 Write('long ' ' string ');
63 Write('Pascal keywords. ');
64 \end{lstlisting}
65
66 A Titled listing:
67 \begin{lstlisting}[language=Pascal,title={A bit of Pascal}]
68 for i:=maxint to 0 do
69 begin
70   { do nothing }
71 end;
72 Write('case insensitive ');
73 \end{lstlisting}
74
75
76 A Captioned listing (known as Listing \ref{pascallisting}) :
77 \begin{lstlisting}[language=Pascal,caption=Another bit of Pascal, label=pascallisting]

```

```

78 for i:=maxint to 0 do
79   begin
80     { do nothing }
81   end;
82 \end{lstlisting}
83
84 \section{An Environment}
85 \begin{lstlisting}[language=Pascal]
86 for i:=maxint to 0 do
87   begin
88     { do nothing }
89   end;
90 \end{lstlisting}
91
92 \lstnewenvironment{colored}[1]{\lstset{language=Pascal,numbers=right,numberstyle
93 \begin{colored}{red}
94 for i:=maxint to 0 do
95   begin
96     { do nothing }
97   end;
98 \end{colored}
99
100 \begin{colored}{blue}
101 for i:=maxint to 0 do
102   begin
103     { do nothing }
104   end;
105 \end{colored}
106
107 \section{Framing and such}
108 \lstset{backgroundcolor=\color[named]{CarnationPink}}
109 \begin{lstlisting}[language=Pascal,frame=single,rulecolor=\color{red}]
110 for i:=maxint to 0 do
111   begin
112     { do nothing }
113   end;
114 \end{lstlisting}
115
116 \begin{lstlisting}[language=Pascal,frameround=tttt,backgroundcolor=\color{yellow}
117 for i:=maxint to 0 do
118   begin
119     { do nothing }
120   end;
121 \end{lstlisting}
122 \lstset{backgroundcolor=}
123 \begin{lstlisting}[language=Pascal,frame=single]

```

```

124 for i:=maxint to 0 do
125   begin
126     { do nothing }
127   end;
128   \end{lstlisting}
129
130 \begin{lstlisting}[language=Pascal,frame=lines]
131 for i:=maxint to 0 do
132   begin
133     { do nothing }
134   end;
135   \end{lstlisting}
136
137 \begin{lstlisting}[language=C,identifierstyle=\slshape,directivestyle=\ttfamily,
138 caption=A C language listing, frame=lines,backgroundcolor={\color[cm]{0,0,0,0.
139 #define EXAMPLE whichwhat
140 x = "foo";
141 break;
142 \end{lstlisting}
143
144 \section{Listing with Math}
145 \begin{lstlisting}[language=c, texcl, commentstyle=\color{green}]
146 // \upshape calculate $a_{ij}$
147 a[i][j] = a[j][j]/a[i][j];
148 \end{lstlisting}
149
150 \begin{lstlisting}[texcl,language=c]
151 // \upshape calculate $a_{ij}$
152 a[i][j] = a[j][j]/a[i][j];
153 \end{lstlisting}
154
155 \begin{lstlisting}[language=c,mathescape,numbers=left,commentstyle=\color{green}]
156 // calculate $a_{ij}$
157 $a_{ij}
158 = a_{jj}/a_{ij}$;
159 // calculate $a_{ij} =
160 \sin x$
161 a[i,j]=sin(x)
162 foo="a word";
163 foo="a $x^2$ math";
164 \end{lstlisting}
165
166 \begin{lstlisting}[language=c,escapechar=\%,escapebegin=\textless,escapeend=\tex
167 // calculate %$a_{ij}$%
168 a_{ij}
169 = a_{jj}/a_{ij};

```

```

170 \end{lstlisting}
171
172 \begin{lstlisting}[language=c,numbers=left,stringstyle=\ttfamily]
173 // calculate  $a_{ij}$ 
174  $a_{ij}$ 
175 =  $a_{jj}/a_{ij}$ ;
176 // calculate  $a_{ij}$  =
177 \sin x$
178 a[i,j]=sin(x)
179 foo="a word";
180 foo="a \"string\"";
181 foo="a  $x^2$  math";
182 \end{lstlisting}
183
184 \section{A Perl Listing}
185 \lstinputlisting[language=perl]{any.sty.ltxml}
186
187 \section{A Recursive \TeX\ listing}
188 \lstinputlisting[language={[LaTeX]TeX}]{listing.tex}
189
190 \section{Testing Tag}
191 % AHA, tagstyle only is in effect with XML (?)
192 \begin{lstlisting}[language=XML,tagstyle=\bf]
193 <element attr='value'>content</element>
194 \end{lstlisting}
195 \begin{lstlisting}[language=XML,tagstyle=\bf,usekeywordsintag=false]
196 <element attr='value'>content</element>
197 \end{lstlisting}
198 \begin{lstlisting}[language=XML,tagstyle=\bf,markfirstintag]
199 <element attr='value'>content</element>
200 \end{lstlisting}
201
202 \section{Screwiness}
203 \lstdefinelanguage{bingo}{morekeywords={foo,bar},morekeywords=[2]{bing,bar}}
204 %,
205 % AHA, words can only be in one class (1st one declared?)
206 % BUT, index is separate, and classname is without the "style" !!
207 \begin{lstlisting}[language=bingo,keywordstyle=\bfseries,keywordstyle={ [2]\itshape}
208 foo bar baz bing booboo
209 \end{lstlisting}
210 {\bfseries\itshape bfit}
211 {\itshape\bfseries itbf}
212 \printindex
213 \end{document}

```


11 Testing Tag

1 `<element attr='value'>content</element>`

1 `<element attr='value'>content</element>`

1 `<element attr='value'>content</element>`

12 Screwiness

1 `foo bar baz bing booboo`

`bfit itbf`